888 Item Maintenance

Functional Group ID=QG

Introduction:

This Draft Standard for Trial Use provides the format and establishes the data contents of the Item Maintenance Transaction Set (888) for use within the context of an Electronic Data Interchange (EDI) environment. This transaction set is used to enable a manufacturer, supplier, broker, or agent to provide detailed finished goods product information to a partner in a consumer goods market. This transaction set can be used to provide information about new products or changes in existing product specifications. Price changes will not be sent with this transaction set, but can be sent with the Price Change Transaction Set (879).

Notes:

- 1. Services/Agencies with weapon system program management responsibilities use this transaction set to communicate information to the Defense Logistics Agency (DLA), which manages supporting component/supporting parts and items. This transaction associates a specific part/item, identified by National Stock Number (NSN), with a specific end item/weapons system, identify by Weapons System Designator Code (WSDC), and associated management data.
- 2. The DLA uses this transaction to respond to Service/Agency activities, giving status of their weapon system application submissions.
- 3. DoD logistics users should refer to the Defense Logistics Management System (DLMS) Supplement to the Federal Implementation Convention (IC) available at URL: http://www.dla.mil/j-6/dlmso. The DLMS Supplement provides specific business rules, conditions, and authorized codes necessary for appropriate use of this IC within the DLMS.

Heading:

Page No. 4	Pos. No. 0100	Seg. <u>ID</u> ST	<u>Name</u> Transaction Set Header	Req. Des. M	Max.Use	Loop <u>Repeat</u>	Notes and Comments
5	0150	BGN	Beginning Segment	O	1		
			LOOP ID - 0100		·	>1	
7	0200	N1	Name	M	1		n1
Not Used	0300	N2	Additional Name Information	O	1		
Not Used	0400	N3	Address Information	O	2		
Not Used	0500	N4	Geographic Location	О	1		
Not Used	0600	N9	Reference Identification	О	10		
Not Used	0700	G61	Contact	O	>1		
Not Used	0800	NTE	Note/Special Instruction	O	20		
Not Used	0850	G93	Price Bracket Identification	O	50		

8	0860	G62	Date/Time	M	1		
			LOOP ID - 0200			>1	
9	0900	LM	Code Source Information	O	1		
10	1000	LQ	Industry Code	M	100		

Detail:

Page <u>No.</u>	Pos. <u>No.</u>	Seg. <u>ID</u>	Name LOOP ID - 0300	Req. Des.	Max.Use	Loop Repeat	Notes and Comments
11	0100	G53	Maintenance Type	M	1	71	
Not Used	0200	G62	Date/Time	O	3		n2
Not Used	0300	NTE	Note/Special Instruction	O	20		
			LOOP ID - 0310			>1	
12	0350	LX	Assigned Number	M	1		
13	0400	G39	Item Characteristics - Vendor's Selling Unit	O	1		
Not Used	0500	G69	Line Item Detail - Description	O	5		
Not Used	0550	QTY	Quantity	O	>1		
Not Used	0560	LIN	Item Identification	O	1		
Not Used	0570	PID	Product/Item Description	O	200		
Not Used	0580	PKG	Marking, Packaging, Loading	O	25		
Not Used	0600	G23	Terms of Sale	O	10		
Not Used	0700	G62	Date/Time	O	2		
Not Used	0800	G36	Price List Reference	O	1		
Not Used	0900	G26	Pricing Conditions	O	2		
Not Used	1000	G43	Promotion/Price List Area	O	9999		
Not Used	1100	G24	Promotion Reference	O	999		
Not Used	1200	G40	Bracket Price	O	99		
Not Used	1300	G93	Price Bracket Identification	O	50		
Not Used	1350	G22	Pricing Information	O	5		
Not Used	1400	G46	Promotion Allowance/Charge	O	99		
Not Used	1450	H1	Hazardous Material	O	5		
Not Used	1500	G54	Module Description	O	99		
16	1510	N9	Reference Identification	O	10		
Not Used	1520	UIT	Unit Detail	O	10		
Not Used	1530	MEA	Measurements	O	10		
Not Used	1540	TD1	Carrier Details (Quantity and Weight)	O	1		
			LOOP ID - 0311			>1	
18	1560	N1	Name	О	1		
Not Used	1570	N2	Additional Name Information	O	2		
Not Used	1580	N3	Address Information	O	2		
Not Used	1590	N4	Geographic Location	O	1		
Not Used	1600	PAL	Pallet Information	0	>1		
Not Used	1610	G93	Price Bracket Identification	O	1		
Not Used	1620	QTY	Quantity	0	1		
0000		~ - *				. 1	
Not Used	1650	CSE	LOOP ID - 0312	0	1	>1	
Not Used	1650	G55	Item Characteristics - Consumer Unit	0	1		
Not Used	1700	G69	Line Item Detail - Description	О	5		

Not Used	1750	QTY	Quantity	O	1			
Not Used	1760	LIN	Item Identification	O	1			
Not Used	1765	PID	Product/Item Description	O	200			
Not Used	1770	H1	Hazardous Material	O	5			
Not Used	1775	REF	Reference Identification	O	10			
Not Used	1780	PKG	Marking, Packaging, Loading	O	25			
Not Used	1785	MEA	Measurements	O	10			
Not Used	1790	TD1	Carrier Details (Quantity and Weight)	O	1			
Not Used	1795	SLN	Subline Item Detail	O	100			
			LOOP ID - 0313			>1		
19	1800	LM	Code Source Information	O	1			
20	1900	LQ	Industry Code	M	100			
21	2000	SE	Transaction Set Trailer	M	1			_

Transaction Set Notes

- 1. One iteration of the N1 loop should be used to identify the buying party (BY) to establish the area or location for which the item maintenance applies.
- **2.** The G62 segment is used to specify the effective date for the item maintenance action reflected in G5301.

Segment: ST Transaction Set Header

Position: 0100

Loop:

Level: Heading Usage: Mandatory

Max Use: 1

Purpose:

To indicate the start of a transaction set and to assign a control number

Syntax Notes:

Semantic Notes:

1 The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

2 The implementation convention reference (ST03) is used by the translation routines of the interchange partners to select the appropriate implementation convention to match the transaction set definition.

	Ref.	Data			
	Des.	Element	<u>Name</u>	Attı	<u>ributes</u>
M	ST01	143	Transaction Set Identifier Code	\mathbf{M}	1 ID 3/3
			Code uniquely identifying a Transaction Set		
			888 Item Maintenance		
M	ST02	329	Transaction Set Control Number	\mathbf{M}	1 AN 4/9
			Identifying control number that must be unique functional group assigned by the originator for a		tion set
			A unique number assigned by the originator of the originator's application program.	^f the transaction s	et, or
	ST03	1705	Implementation Convention Reference	o	1 AN 1/35
			Reference assigned to identify Implementation (Convention	

Segment: BGN Beginning Segment

Position: 0150

Loop:

Level: Heading Usage: Optional

Max Use: 1

Purpose: To indicate the beginning of a transaction set

Syntax Notes: 1 If BGN05 is present, then BGN04 is required.
 Semantic Notes: 1 BGN02 is the transaction set reference number.

2 BGN03 is the transaction set date.

3 BGN04 is the transaction set time.

4 BGN05 is the transaction set time qualifier.

5 BGN06 is the transaction set reference number of a previously sent transaction affected by the current transaction.

Data Element Summary

			Data Element Summary							
	Ref.	Data								
	Des.	Element	<u>Name</u>	At	trib	utes				
M	BGN01	353	Transaction Set Purpose Code	\mathbf{M}	1	ID 2/2				
			Code identifying purpose of transaction set							
			00 Original							
M	BGN02	127	Reference Identification	\mathbf{M}	1	AN 1/50				
			Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier							
			Use code "Z" for this data element to satisfy mandato requirements.	ory X12 sy	yntax	r				
M	BGN03	373	Date	\mathbf{M}	1	DT 8/8				
			Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year							
			This date corresponds to the Universal Time Coordinate	ate (UTC).					
	BGN04	337	Time	X	1	TM 4/8				
			Time expressed in 24-hour clock time as follows: HHM or HHMMSSD, or HHMMSSDD, where $H = hours$ (00 (00-59), $S = integer$ seconds (00-59) and $DD = decima$ seconds are expressed as follows: $D = tenths$ (0-9) and (00-99)	0-23), M = 1 seconds	= mi ; dec	nutes imal				
			1. Express the originating activity's time in UTC.							
			2. Express time in a four-position (HHMM) format							
Not Used	BGN05	623	Time Code	O	1	ID 2/2				
			Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an							

004030F888W0 5 April 20, 2004

indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the

codes that follow

Not Used	BGN06	127	Reference Identi	fication	O	1	AN 1/50
				ation as defined for a particular Transac reference Identification Qualifier	tion Se	t or	as
	BGN07	640	Transaction Typ	e Code	O	1	ID 2/2
			Code specifying t	he type of transaction			
			W1	Weapons Data Change			
	BGN08	306	Action Code		O	1	ID 1/2
			Code indicating ty	ype of action			
			RS	Report Status			
Not Used	BGN09	786	Security Level C	ode	O	1	ID 2/2
			Code indicating the information follow	ne level of confidentiality assigned by the wing	ne send	er to	the

Segment: N1 Name

Position: 0200

Loop: 0100 Mandatory

Level: Heading Usage: Mandatory

Max Use: 1

Purpose: To identify a party by type of organization, name, and code

Syntax Notes: 1 At least one of N102 or N103 is required.

2 If either N103 or N104 is present, then the other is required.

Semantic Notes:

Notes: Must use to identify the organization sending the transaction.

	Ref.	Data		•			
	Des.	Element	<u>Name</u>		At	trib	utes
M	N101	98	Entity Identi	fier Code	M	1	ID 2/3
			Code identify an individual	ing an organizational entity, a physical loca	tion, pr	opei	rty or
			55	Service Manager			
			ICP	Inventory Control Point			
Not Used	N102	93	Name		\mathbf{X}	1	AN 1/60
			Free-form nar	me			
Must Use	N103	66	Identification	n Code Qualifier	\mathbf{X}	1	ID 1/2
			Code designate Identification	ting the system/method of code structure use Code (67)	ed for		
			M4	Department of Defense Routing Iden	tifier C	ode	(RIC)
Must Use	N104	67	Identification	n Code	X	1	AN 2/80
			Code identify	ing a party or other code			
Not Used	N105	706	Entity Relati	onship Code	O	1	ID 2/2
			Code describi	ng entity relationship			
Must Use	N106	98	Entity Identi	fier Code	O	1	ID 2/3
			Code identify an individual	ing an organizational entity, a physical loca	tion, pr	ope	rty or
			FR	Message From			
				Must use to indicate that the organize N104 is originating the transaction s		cited	! in

Segment: G62 Date/Time

Position: 0860

Loop:

Level: Heading Usage: Mandatory

Max Use: 1

Purpose: To specify pertinent dates and times

Syntax Notes: 1 At least one of G6201 or G6203 is required.

2 If either G6201 or G6202 is present, then the other is required.

3 If either G6203 or G6204 is present, then the other is required.

Semantic Notes:

Data Element Summary

	Ref.	Data					
	Des.	Element	Name		Attı	<u>rib</u> ı	utes
Must Use	G6201	432	Date Qualifier		X	1	ID 2/2
			Code specifying type of date				
			BB Transaction Control Date	e			
Must Use	G6202	373	Date		X	1	DT 8/8
			Date expressed as CCYYMMDD where CC of the calendar year	represents the	first tv	vo c	ligits
Not Used	G6203	176	Time Qualifier		X	1	ID 1/2
			Code specifying the reported time				
Not Used	G6204	337	Time		X	1	TM 4/8
			Time expressed in 24-hour clock time as foll or HHMMSSD, or HHMMSSDD, where H = $(00-59)$, S = integer seconds $(00-59)$ and DD seconds are expressed as follows: D = tenths $(00-99)$	= hours (00-23) 0 = decimal seco), M = onds; o	mi dec	nutes imal
Not Used	G6205	623	Time Code		O	1	ID 2/2
			Code identifying the time. In accordance wit	h International	Stand	ard	s

Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow

Segment: LM Code Source Information

Position: 0900

Loop: 0200 Optional

Level: Heading Usage: Optional Max Use: 1

Purpose: To transmit standard code list identification information

Syntax Notes: Semantic Notes:

M	Ref. <u>Des.</u> LM01	Data <u>Element</u> 559		alifier Code	<u>At</u> M	trib 1	utes ID 2/2
			Code identi	fying the agency assigning the code values Department of Defense (DoD)			
Not Used	LM02	822	Source Sub	• , ,	O	1	AN 1/15
			A reference Qualifier	that indicates the table or text maintained by	the So	ırce	

Segment: LQ Industry Code

Position: 1000

Loop: 0200 Optional

Level: Heading
Usage: Mandatory
Max Use: 100

Purpose: Code to transmit standard industry codesSyntax Notes: 1 If LQ01 is present, then LQ02 is required.

Semantic Notes:

	Ref.	Data					
	Des.	Element	Name		A	ttrib	utes
Must Use	LQ01	1270	Code List	Qualifier Code	O	1	ID 1/3
			Code ident	ifying a specific industry code list			
			0	Document Identification Code			
Must Use	LQ02	1271	Industry (Code	X	1	AN 1/30
			Code indic	ating a code from a specific industry code list			

Segment: G53 Maintenance Type

Position: 0100

Loop: 0300 Mandatory

Level: Detail
Usage: Mandatory

Max Use: 1

Purpose: To identify the specific type of item maintenance

Syntax Notes: Semantic Notes:

	Ref. <u>Des.</u>	Data <u>Element</u>	<u>Name</u>		At	trib	<u>utes</u>
M	G5301	875	Maintenand	ce Type Code	M	1	ID 3/3
			Code identif	Tying the specific type of item maintenance			
			020	Assignment			
			022	Change in Status			

Segment: LX Assigned Number

Position: 0350

Loop: 0310 Mandatory

Level: Detail
Usage: Mandatory

Max Use: 1

Purpose: To reference a line number in a transaction set

Syntax Notes: Semantic Notes:

Data Element Summary

	Ref.	Data		
	Des.	Element	<u>Name</u>	<u>Attributes</u>
M	LX01	554	Assigned Number	M 1 N0 1/6

Number assigned for differentiation within a transaction set

In the first 2/LX/0350 loop iteration, cite numeric 1. If subsequent loop iterations are used, increase incrementally by 1.

Segment: G39 Item Characteristics - Vendor's Selling Unit

Position: 0400

Loop: 0310 Mandatory

Level: Detail
Usage: Optional
Max Use: 1

Purpose: To identify a vendor's selling unit or to provide physical characteristics relative to a

vendor's selling unit

Syntax Notes: 1 At least one of G3901 or G3902 is required.

2 If either G3902 or G3903 is present, then the other is required.

3 If any of G3905 G3906 or G3907 is present, then all are required.

4 If either G3906 or G3907 is present, then the other is required.

5 If either G3908 or G3909 is present, then the other is required.

6 If either G3910 or G3911 is present, then the other is required.

7 If either G3912 or G3913 is present, then the other is required.

8 If either G3914 or G3915 is present, then the other is required.

9 If either G3918 or G3919 is present, then the other is required.

10 If either G3923 or G3924 is present, then the other is required.

11 If either G3925 or G3926 is present, then the other is required.

Semantic Notes:

	Ref.	Data	·					
	Des.	Element	<u>Name</u>	Attributes				
Not Used	G3901	438	U.P.C. Case Code	X	1	AN 12/12		
			Code (Universal Product Code - U.P.C.) including two high order digits identifying the "system" (U.S. Grocery = 00, 06 or 07; U.S. Drug = 03); using the U.S. Grocery system, the next ten digits are: Manufacturer (5) Case Code (5)					
	G3902	235	Product/Service ID Qualifier	X	1	ID 2/2		
			Code identifying the type/source of the descriptive number Product/Service ID (234)	r used	in			
			FS National Stock Number					
	G3903	234	Product/Service ID	X	1	AN 1/48		
			Identifying number for a product or service					
Not Used	G3904	152	Special Handling Code	O	1	ID 2/3		
			Code specifying special transportation handling instruction	ns				
Not Used	G3905	395	Unit Weight	X	1	R 1/8		
			Numeric value of weight per unit					
Not Used	G3906	187	Weight Qualifier	X	1	ID 1/2		
			Code defining the type of weight					
Not Used	G3907	188	Weight Unit Code	X	1	ID 1/1		
			Code specifying the weight unit					

Not Used	G3908	65	Height Vertical dimension of an object measured when the object	X ect is in a		R 1/8
			position	7Ct 18 111	uie u	iprigiit
Not Used	G3909	355	Unit or Basis for Measurement Code	X	1	ID 2/2
			Code specifying the units in which a value is being exprining which a measurement has been taken	essed, o	r ma	nner
Not Used	G3910	189	Width	X	1	R 1/8
			Shorter measurement of the two horizontal dimensions object in the upright position	measure	d wi	th the
Not Used	G3911	355	Unit or Basis for Measurement Code	X	1	ID 2/2
			Code specifying the units in which a value is being exprining which a measurement has been taken	essed, o	r ma	nner
Not Used	G3912	82	Length	X	1	R 1/8
			Largest horizontal dimension of an object measured whe the upright position	en the ol	bject	is in
Not Used	G3913	355	Unit or Basis for Measurement Code	X	1	ID 2/2
			Code specifying the units in which a value is being exprining which a measurement has been taken	essed, o	r ma	nner
Not Used	G3914	183	Volume	X	1	R 1/8
			Value of volumetric measure			
Not Used	G3915	355	Unit or Basis for Measurement Code	X	1	ID 2/2
			Code specifying the units in which a value is being exprining which a measurement has been taken	essed, o	r ma	nner
Not Used	G3916	416	Pallet Block and Tiers	0	1	N0 6/6
			Code indicating pallet and load structure; first three digit number of cases per layer, last three digits indicate the r per pallet			
Not Used	G3917	356	Pack	O	1	N0 1/6
			The number of inner containers, or number of eaches if containers, per outer container	there are	e no	inner
Not Used	G3918	357	Size	X	1	R 1/8
			Size of supplier units in pack			
Not Used	G3919	355	Unit or Basis for Measurement Code	X	1	ID 2/2
			Code specifying the units in which a value is being exprining which a measurement has been taken	essed, o	r ma	nner
Not Used	G3920	397	Color	O	1	AN 1/10
			Free-form description of color			
Not Used	G3921	398	Order Sizing Factor	O	1	R 1/10
			A product specification other than gross or net weight, of line item or transaction used for order sizing and pricing			for a
Not Used	G3922	876	Alternate Tiers per Pallet	O	1	ID 1/3
			Number indicating the alternate tiers per pallet structure represent the number of tiers per pallet	; the thr	ee di	igits

Not Used	G3923	235	Product/Service ID Qualifier		1	ID 2/2
			Code identifying the type/source of the descriptive number Product/Service ID (234)	r used	in	
Not Used	G3924	234	Product/Service ID	X	1	AN 1/48
			Identifying number for a product or service			
Not Used	G3925	187	Weight Qualifier	X	1	ID 1/2
			Code defining the type of weight			
Not Used	G3926	395	Unit Weight	X	1	R 1/8
			Numeric value of weight per unit			
Not Used	G3927	810	Inner Pack	O	1	N0 1/6
			The number of eaches per inner container			
Not Used	G3928	103	Packaging Code	O	1	AN 3/5
			Code identifying the type of packaging; Part 1: Packaging Packaging Material; if the Data Element is used, then Part required			
Not Used	G3929	878	Cash Register Item Description	O	1	AN 1/20
			The cash register description of an item			

Segment: N9 Reference Identification

Position: 1510

Loop: 0310 Mandatory

Level: Detail
Usage: Optional
Max Use: 10

Purpose: To transmit identifying information as specified by the Reference Identification

Qualifier

Syntax Notes: 1 At least one of N902 or N903 is required.

2 If N906 is present, then N905 is required.

3 If either C04003 or C04004 is present, then the other is required.

4 If either C04005 or C04006 is present, then the other is required.

Semantic Notes: 1 N906 reflects the time zone which the time reflects.

2 N907 contains data relating to the value cited in N902.

Notes: Use multiple repetitions as needed to identify the weapon system and other related

relevant information.

			Dui	a Element Summary						
	Ref.	Data								
	Des.	Element	<u>Name</u>		Attributes					
M	N901	128	Reference	Identification Qualifier	M	1	ID 2/3			
			Code quali	fying the Reference Identification						
			IW	Part Interchangeability						
			W2	Weapon System Number						
			XA	Substitute National Stock Number						
	N902	127	Reference	Identification	X	1	AN 1/50			
				information as defined for a particular Transact y the Reference Identification Qualifier	ion Se	t or	as			
	N903	369	Free-form	Description	X	1	AN 1/45			
			Free-form	descriptive text						
Not Used	N904	373	Date		O	1	DT 8/8			
			Date expre of the cale	ssed as CCYYMMDD where CC represents the ndar year	e first t	two	digits			
Not Used	N905	337	Time		X	1	TM 4/8			
			or HHMM (00-59), S	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where $H = hours (00-23)$, $M = minutes (00-59)$, $S = integer seconds (00-59)$ and $DD = decimal seconds$; decimal seconds are expressed as follows: $D = tenths (0-9)$ and $DD = hundredths (00-99)$						
Not Used	N906	623	Time Cod	e	O	1	ID 2/2			
			Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow							

Not Used	N907	C040	Reference Identifier	O	1
			To identify one or more reference numbers or identification specified by the Reference Qualifier	on num	bers as
Not Used	C04001	128	Reference Identification Qualifier	\mathbf{M}	ID 2/3
			Code qualifying the Reference Identification		
Not Used	C04002	127	Reference Identification	\mathbf{M}	AN 1/50
			Reference information as defined for a particular Transac specified by the Reference Identification Qualifier	ction Se	t or as
Not Used	C04003	128	Reference Identification Qualifier	X	ID 2/3
			Code qualifying the Reference Identification		
Not Used	C04004	127	Reference Identification	X	AN 1/50
			Reference information as defined for a particular Transac specified by the Reference Identification Qualifier	ction Se	t or as
Not Used	C04005	128	Reference Identification Qualifier	X	ID 2/3
			Code qualifying the Reference Identification		
Not Used	C04006	127	Reference Identification	X	AN 1/50
			Reference information as defined for a particular Transac specified by the Reference Identification Qualifier	ction Se	t or as

Segment: N1 Name

Position: 1560

Loop: 0311 Optional

Level: Detail
Usage: Optional

Max Use: 1

Purpose: To identify a party by type of organization, name, and code

Syntax Notes: 1 At least one of N102 or N103 is required.

2 If either N103 or N104 is present, then the other is required.

Semantic Notes:

Notes: Must use to identify the organization receiving the transaction.

	Ref.	Data		·					
	Des.	Element	<u>Name</u>		<u>Attributes</u>				
M	N101	98	Entity Ide	entifier Code	M	1	ID 2/3		
			Code ident	tifying an organizational entity, a physical locational	on, pr	oper	ty or		
			55	Service Manager					
			ICP	Inventory Control Point					
Not Used	N102	93	Name		X	1	AN 1/60		
			Free-form	name					
Must Use	N103	66	Identifica	tion Code Qualifier	\mathbf{X}	1	ID 1/2		
			-	gnating the system/method of code structure used ion Code (67)	l for				
			M4	Department of Defense Routing Identif	fier C	ode	(RIC)		
Must Use	N104	67	Identifica	tion Code	\mathbf{X}	1	AN 2/80		
			Code ident	tifying a party or other code					
Not Used	N105	706	Entity Rel	lationship Code	O	1	ID 2/2		
			Code desc	ribing entity relationship					
Must Use	N106	98	Entity Ide	entifier Code	O	1	ID 2/3		
			Code ident	tifying an organizational entity, a physical locational	on, pr	oper	ty or		
			TO	Message To					

Segment: LM Code Source Information

Position: 1800

Loop: 0313 Optional

Level: Detail
Usage: Optional

Max Use: 1

Purpose: To transmit standard code list identification information

Syntax Notes: Semantic Notes:

	Ref.	Data Element	Nome	·	A 4	4	4 -a
	Des.	Element			A	trib	
M	LM01	559	Agency Q	ualifier Code	\mathbf{M}	1	ID 2/2
			Code iden	tifying the agency assigning the code values			
			DF	Department of Defense (DoD)			
Not Used	LM02	822	Source Su	bqualifier	O	1	AN 1/15
			A reference Qualifier	te that indicates the table or text maintained by	the Sou	ırce	

Segment: LQ Industry Code

Position: 1900

Loop: 0313 Optional

Level: Detail
Usage: Mandatory

Max Use: 100

Purpose: Code to transmit standard industry codesSyntax Notes: 1 If LQ01 is present, then LQ02 is required.

Semantic Notes:

Data Element Summary

	Ref.	Data					
	Des.	Element	<u>Name</u>		A	ttrib	utes
Must Use	LQ01	1270	Code List Qualif	ier Code	O	1	ID 1/3
			Code identifying a	a specific industry code list			
			80	Advice Code			
			81	Status Code			
			FF	Essentiality Code			
			FG	Source Maintenance and Recoverabi	lity Co	ode	
			LM	Case Origin Code			
Must Use	LQ02	1271	Industry Code		X	1	AN 1/30
			~				

Code indicating a code from a specific industry code list

Segment: **SE** Transaction Set Trailer

Position: 2000

Loop:

Level: Detail
Usage: Mandatory

Max Use: 1

Purpose: To indicate the end of the transaction set and provide the count of the transmitted

segments (including the beginning (ST) and ending (SE) segments)

Syntax Notes:

Semantic Notes:

M	Ref. <u>Des.</u> SE01	Data <u>Element</u> 96	Name Number of Included Segments	At M	trib 1	utes N0 1/10		
			Total number of segments included in a transaction set inc SE segments	luding	g ST	and		
\mathbf{M}	SE02	329	Transaction Set Control Number	M	1	AN 4/9		
			Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set					
			Cite the same number as the one cited in ST02.					